

## **Patent Abstracts of Japan**

PUBLICATION NUMBER : 04010925 PUBLICATION DATE : 16-01-92

APPLICATION DATE : 27-04-90 APPLICATION NUMBER : 02112300


APPLICANT: DAIKYO INC;

INVENTOR: FUJIMURA KOZO;

INT.CL. : B32B 7/02 B32B 7/02 B32B 33/00

TITLE : LAMINATED MOLDING OF

THERMOSETTING RESIN



## ABSTRACT:

PURPOSE: To enhance a quality feeling and to carry out molding using only a protruding mold by constituting a resin compound layer on the rear side of a gel coat layer and an FRP layer.

CONSTITUTION: A colored gel coat layer 1, a fiber reinforced plastic layer 2 and a resin compound layer 3 being a resin layer containing 60wt.% or more of a filler and having Young's modulus of 500kg/mm² or less and the coefficient of linear expansion of  $2.0 \times 10^{-5}$  or less are formed in this order on the surface side of a product. The surface gel coat layer 1 is formed as a transparent resin layer or a lightly colored transparent resin layer and the fiber reinforced plastic layer 2 is formed by impregnating a glass fiber with an unsaturated polyester resin. The resin compound layer 3 is constituted as a considerably thick layer by adding a filler to a transparent resin for the purpose of imparting strength and prepared as a transparent layer, an opaque layer or a translucent layer slightly transmitting light. A bathtub composed of this laminated molded body generates a deep sound if struck without being deformed and can be simply prepared only by a protruding mold at the time of molding.

COPYRIGHT: (C)1992,JPO&Japio